



Standard Features

- 24" On-Center C-Channel Floor Crossmembers
- 24" On-Center Tube Wall Studs
- 24" On-Center Tube Roof Bows
- 2" A-Frame Coupler
- Safety Chains
- 15" Deep Wedge (4', 5', and 6' Wides Only)
- 18" Deep Wedge (7' Wide Only)
- 4-Way Molded Plug (4', 5', 6', 7' Wide 3K Only)
- 7-Way RV Style Molded Plug
- Breakaway Switch with Battery
- 32" x 64" RV Side Door
- Plastic Door Holders
- 1150 lb. Rated Rear Ramp Door
- Barlocks on Ramp Door
- Aluminum Fenders
- WideTrac Full width interior walls without fender boxes
- 4" Drop Spring Axles

- Easy Lube Hubs
- Silver Wheels
- Fully Painted Frame
- Polyethylene Vapor Barrier
- .030 Smooth Aluminum Exterior
- Semi-Screw-less (Seams Screwed w/ Color Matching Screws)
- Seamless Aluminum Roof
- Aluminum Bottom Trim
- 16" ATP Stoneguard w/ Top Trim
- Flow-Through Scoop Vents
- 5.2 mm Lauan Wall Liner w/ Vinyl H-Molding
- 3/4" Engineered Wood Floor
- (1) 12 Volt Wall mounted LED Dome Light w/ 1 Wall Switch
- LED Slimline Lights and 3/4" Bullet Marker Lights (All Clear Lens)

Options

- Ramp Options
- Door Options
- Electrical Options
- Color Options
- Contact your local dealer for more options



Stock-Aide Flat Top V-Nose SA

		5' Wide (3K)	6' Wide (3K)	6' Wide w/ Brakes (3.5K)	7' Wide (3K)	7' Wide w/ Brakes (3.5K)	7' Wide w/ Brakes (5K)
Model	6'	-	-	-	-	-	-
	8'	Y6008SA-030	-	-	-	-	-
	10'	Y6010SA-030	Y7210SA-030	Y7210SA-035	-	-	-
	12'	Y6012SA-030	Y7212SA-030	Y7212SA-035	Y8412SA-030	Y8412SA-035	Y8412SA-050
	14'	-	Y7214SA-030	-	-	-	-
GVWR (lb. / Axle)		2990	2990	3500	2990	3500	5000
GAWR (lb. / Axle)		3500	3500	3500	3500	3500	5000
Curb Weight	6'	-	-	-	-	-	-
	8'	890	-	-	-	-	-
	10'	960	995	995	-	-	-
	12'	1030	1200	1200	1340	1340	1340
	14'	-	1305	-	-	-	-
Payload	6'	-	-	-	-	-	-
	8'	2100	-	-	-	-	-
	10'	2030	1995	2505	-	-	-
	12'	1960	1790	2300	1650	2160	3660
	14'	-	1685	-	-	-	-
Frame		3"x2" Tube	3"x2" Tube	3"x2" Tube	4"x2" Tube	4"x2" Tube	4"x2" Tube
Cross Members		24" On-Center C-Channel Floor Crossmembers		24" On-Center C-Channel Floor Crossmembers		24" On-Center C-Channel Floor Crossmembers	
Tongue		3"x2" Tube	3"x2" Tube	3"x2" Tube	4"x2" Tube	4"x2" Tube	4"x2" Tube
Wall Studs		24" On-Center Tube Wall Studs		24" On-Center Tube Wall Studs		24" On-Center Tube Wall Studs	
Roof Bows		24" On-Center Tube Roof Bows		24" On-Center Tube Roof Bows		24" On-Center Tube Roof Bows	
Coupler		2" A-Frame Coupler		2" A-Frame Coupler		2" A-Frame Coupler	
Jack		2K Zinc Plated Jack		2K Zinc Plated Jack		2K Zinc Plated Jack	
Fenders		Aluminum Fenders		Aluminum Fenders		Aluminum Fenders	
Easy Lube Axles		4" Drop Spring Axles		4" Drop Spring Axles		4" Drop Spring Axles	
Tires		205/75R15 LRC	205/75R15 LRC	205/75R15 LRC	205/75R15 LRC	205/75R15 LRC	225/75R15 LRD
Wheels		15" Silver Wheels		15" Silver Wheels		15" Silver Wheels	
Flooring		3/4" Engineered Wood Floor		3/4" Engineered Wood Floor		3/4" Engineered Wood Floor	
Lights		LED Slimline Lights and 3/4" Bullet		LED Slimline Lights and 3/4" Bullet Marker Lights		LED Slimline Lights and 3/4" Bullet Marker Lights	
Electric Plug		4-Way Molded Plug		7-Way RV Style Molded Plug	4-Way Molded Plug	7-Way RV Style Molded Plug	
Exterior		.030 Smooth Aluminum Exterior		.030 Smooth Aluminum Exterior		.030 Smooth Aluminum Exterior	
Overall Length	6'	-	-	-	-	-	-
	8'	12'	-	-	-	-	-
	10'	13' 6"	14'	14'	-	-	-
	12'	15' 6"	16'	16'	16'	16'	16'
	14'	-	18'	-	-	-	-
Overall Width		80"	80"	80"	102"	102"	102"
Overall Height		84"	90"	90"	90"	90"	92"
Interior Height		66"	72"	72"	72"	72"	72"
Interior Length	6'	-	-	-	-	-	-
	8'	8' 9"	-	-	-	-	-
	10'	10' 9"	11'	11'	-	-	-
	12'	11' 9"	13'	13'	13' 2"	13' 2"	13' 2"
	14'	-	15'	-	-	-	-
Interior Width		57"	69"	69"	81"	81"	81"
Floor Height		18"	18"	18"	18"	18"	20"
Ramp Door Capacity (lb.)		1150	1150	1150	1150	1150	1150