

FLAT TOP FLAT FRONT 7K

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24				
	Y10216HLFCH-TA-	Y10218HLFCH-TA-	Y10220HLFCH-TA-	Y10222HLFCH-TA-	Y10224HLFCH-TA-				
Model #	070	070	070	070	070				
CAPACITIES									
GVWR (lbs)			7000						
GAWR (lbs/axle)			3500						
Curb Weight	30	3000 3300 3450 3100							
Payload	4000 3700 3550								
CHASSIS		•			3900				
	CH = OH OL = LT to L. T. L.								
Tongue		_	6" x 2" Steel Triple Tube						
Crossmembers		Fe	ormed Steel, 16" On-Cen	ter					
Coupler			2-5/16" A-Frame						
Safety Chains			DOT Compliant						
Tongue Jack			2K Coupler Mounted						
Wall Studs		Steel Tube, 16" On-Center							
Roof Bows	Steel Tube, 24" On-Center								
Front Profile			Flat						
Beavertail	32"			8"					
Ramp(s)	4000 lb. with Assist								
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback								
Vents			Sidewall Airflow						
Fenders			Smooth Aluminum						
Axle		(2)	3500 lb. Drop Spring Br	ake					
Hubs			Easy Lube						
Tires			ST205/75R15C 6-PR						
Wheels			15", 5-Hole Steel						
Exterior Finish			.030" Aluminum						
Undercoating			Automotive						
Protective Coating(s)			Barrier, Textured Polyur	-					
Exterior Fastening			on Seams, VHB Bonded	·					
Exterior Trim		3" Bot	tom Extrusion, 3" Top Ex	trusion					
Stone Guard			24" ATP						
Roof		FI	at Top Seamless Alumin	um					
Interior Walls			Engineered Wood						
Interior Trim			Vinyl Wall Transitions						
Flooring			3/4" Engineered Wood						
Interior Lights			(1) LED						
Switches			(1) Dome Light, 12V						
Connector Plug			Round 7-pin Blade						
Exterior Lights			Full LED, DOT Compliant						







FLAT TOP FLAT FRONT 7K

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24
DIMENSIONS					
Overall Length	252"	276"	300"	324"	
Deck Length	189"	213"	237"	261"	
Deck Width					
Deck Height					





	8.5 x 16	8.5 x 18	0 F v 20	0 F v 22	8.5 x 24	8.5 x 28			
	Y10216HLFVCH-	Y10218HLFVCH-	8.5 x 20 Y10220HLFVCH-	8.5 x 22 Y10222HLFVCH-	Y10224HLFVCH-	Y10228HLFVCH-			
Model #	TA-100	TA-100	TA-100	TA-100	TA-100	TA-100			
CAPACITIES	1A-100	1A-100	1A-100	1A-100	1A-100	1A-100			
GVWR (lbs)	9900								
GAWR (lbs/axle)	0450	5200							
Curb Weight	3150	3275	3425	3575	3725	4025			
Payload	6750	6625	6475	6325	6175	5875			
CHASSIS	ASSIS CONTRACTOR OF THE PROPERTY OF THE PROPER								
Tongue			6" x 2" Stee	l Triple Tube					
Crossmembers			Formed Steel,	16" On-Center					
Integrated Step(s)				Recessed					
Coupler				A-Frame					
Safety Chains			DOT Co	mpliant					
Tongue Jack			2K Couple	er Mounted					
Wall Studs	Steel Tube, 16" On-Center								
Roof Bows	Steel Tube, 24" On-Center								
Front Profile	V-Nose								
Beavertail	32" 48"								
Ramp(s)	4000 lb. with Assist								
Side Door	48" Wide Flush Lock, Cast Aluminum Holdback								
Vents		Sidewall Airflow							
Fenders				Aluminum					
Axle				op Spring Brake					
Hubs				Lube					
Breakaway			•	h, and Lanyard					
Tires				R15D 8-PR					
Wheels			•	ole Steel					
Exterior Finish				luminum					
Undercoating				notive					
Protective Coating(s)			•	tured Polyurea all Ex	•				
Exterior Fastening		Color Matching		VHB Bonded Field (S	emi-Screwless)				
Exterior Trim				on, 3" Top Extrusion					
Stone Guard				ATP					
Interior Walls			-	red Wood					
Interior Trim			•	Transitions					
Ceiling				lation					
Flooring				eered Wood					
Interior Lights				LED					
Switches			(1) Dome	Light, 12V					







	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 28		
Cargo Control			(4) 6000 lb. Re	cessed D-Rings				
Connector Plug		Round 7-pin Blade						
Exterior Lights	Full LED, DOT Compliant							
DIMENSIONS								
Overall Length		276"	300"	324"	348"			
Deck Length		237"	261"	285"	309"			
Deck Width	97"							
Deck Height			2:	2"				





	8.5 x 20
Model #	Y10220HLFVCH-TA-140
CAPACITIES	
GVWR (lbs)	14000
GAWR (lbs/axle)	7000
Curb Weight	3150
Payload	10850
CHASSIS	
Tongue	6" x 2" Steel Triple Tube
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" A-Frame
Safety Chains	DOT Compliant
Tongue Jack	7K Drop Leg, Set-Back
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 24" On-Center
Front Profile	V-Nose
Beavertail	48"
Ramp(s)	4000 lb. with Assist
Side Door	48" Wide Flush Lock, Cast Aluminum Holdback
Vents	Sidewall Airflow
Fenders	Smooth Aluminum
Axle	(2) 7000 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST235/80R16E 10-PR
Wheels	17.5", 8-Hole Steel
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel
Exterior Fastening	Color Matching Screws on Seams, VHB Bonded Field (Semi-Screwless)
Exterior Trim	3" Bottom Extrusion, 3" Top Extrusion
Stone Guard	24" ATP
Interior Walls	Engineered Wood
Interior Trim	Vinyl Wall Transitions
Ceiling	Insulation
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Dome Light, 12V
Cargo Control	(4) 6000 lb. Recessed D-Rings







	8.5 x 20
Connector Plug	Round 7-pin Blade
Exterior Lights	Full LED, DOT Compliant







FLAT TOP FLAT FRONT 10K

	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28			
10 - J - J - J - J	Y10218HLFCH-	Y10220HLFCH-	Y10222HLFCH-	Y10224HLFCH-	Y10226HLFCH-	Y10228HLFCH-			
Model #	TA-100	TA-100	TA-100	TA-100	TA-100	TA-100			
CAPACITIES									
GVWR (lbs)			99	000					
GAWR (lbs/axle)		5200							
Curb Weight	3125	3125 3425 3575 3725 3875 40							
Payload	6775	6475	6325	6175	6025	5875			
CHASSIS									
Tongue	6" x 2" Steel Triple Tube								
Crossmembers				16" On-Center					
Coupler			2-5/16"	A-Frame					
Safety Chains			DOT Co	mpliant					
Tongue Jack			2K Couple	r Mounted					
Wall Studs		Steel Tube, 16" On-Center							
Roof Bows		Steel Tube, 24" On-Center							
Front Profile	Flat								
Beavertail	48"								
Ramp(s)		4000 lb. with Assist							
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback								
Vents		Sidewall Airflow							
Fenders				Aluminum					
Axle			• • •	op Spring Brake					
Hubs			·	Lube					
Tires				R15D 8-PR					
Wheels			•	ole Steel					
Exterior Finish				luminum					
Undercoating		51.41		notive	10: 1				
Protective Coating(s)			ne Vapor Barrier, Tex	•	•				
Exterior Fastening Exterior Trim		Color Matching	Screws on Seams, '	•	emi-Screwiess)				
Stone Guard				on, 3" Top Extrusion ATP					
Roof				less Aluminum					
Interior Walls				red Wood					
Interior Trim				Transitions					
Flooring			•	eered Wood					
Interior Lights				LED					
Switches			, ,	Light, 12V					
Connector Plug			* *	pin Blade					
Exterior Lights				T Compliant					







FLAT TOP FLAT FRONT 10K

	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	
DIMENSIONS							
Overall Length	276"	300"	324"	348"	372"		
Deck Length	213"	237"	261"	285"	309"		
Deck Width	97"						
Deck Height	22"						





	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24					
Model #	Y10216HLFVCH-TA-	Y10218HLFVCH-TA-	Y10220HLFVCH-TA-	Y10222HLFVCH-TA-	Y10224HLFVCH-TA-					
Wouei #	070	070	070	070	070					
CAPACITIES										
GVWR (lbs)			7000							
GAWR (lbs/axle)			3500							
Curb Weight	3000	3150	3300	3450	3100					
Payload	4000	3850	3700	3550	3900					
CHASSIS										
Tongue			6" x 2" Steel Triple Tube							
Crossmembers		Fo	ormed Steel, 16" On-Cent							
Integrated Step(s)			Interior Recessed							
Coupler			2-5/16" A-Frame							
Safety Chains			DOT Compliant							
Tongue Jack			2K Coupler Mounted							
Wall Studs	Steel Tube, 16" On-Center									
Roof Bows	Steel Tube, 24" On-Center									
Front Profile	V-Nose									
Beavertail	32" 48"									
Ramp(s)			4000 lb. with Assist							
Side Door		48" Wide F	lush Lock, Cast Aluminui	m Holdback						
Vents			Sidewall Airflow							
Fenders			Smooth Aluminum							
Axle		(2)	3500 lb. Drop Spring Br	ake						
Hubs			Easy Lube							
Breakaway 		В	attery, Switch, and Lanya	rd						
Tires			ST205/75R15C 6-PR							
Wheels			15", 5-Hole Steel							
Exterior Finish			.030" Aluminum							
Undercoating		Dalvathylana Vanar	Automotive	on all Europed Staal						
Protective Coating(s) Exterior Fastening			Barrier, Textured Polyuron Seams, VHB Bonded	•						
Exterior Trim			tom Extrusion, 3" Top Ex	• • • • • • • • • • • • • • • • • • • •						
Stone Guard		3 800	24" ATP	uusioii						
Interior Walls			Engineered Wood							
Interior Trim			Vinyl Wall Transitions							
Ceiling			Insulation							
Flooring			3/4" Engineered Wood							
Interior Lights			(2) LED							
Switches			(1) Dome Light, 12V							



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

© 2025 Novae LLC





	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24		
Cargo Control	(4) 6000 lb. Recessed D-Rings						
Connector Plug	Round 7-pin Blade						
Exterior Lights	Full LED, DOT Compliant						
DIMENSIONS							
Overall Length	252"	276"	300"	324"			
Deck Length	213"	237"	261"	285"			
Deck Width	97"						
Deck Height		2	0"				

